

US009553368B1

(12) United States Patent

Tonn

(54) MULTI-BAND CABLE ANTENNA WITH IRREGULAR REACTIVE LOADING

- (71) Applicant: David A. Tonn, Amston, CT (US)
- (72) Inventor: **David A. Tonn**, Amston, CT (US)
- (73) Assignee: The United States of America as represented by the Secretary of the

Navy, Washington, DC (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 213 days.

- (21) Appl. No.: 14/532,063
- (22) Filed: Nov. 4, 2014
- (51) Int. Cl. *H01Q 9/14* (2006.01) *H01Q 9/30* (2006.01)
- (52) U.S. Cl. CPC *H01Q 9/145* (2013.01); *H01Q 9/30* (2013.01)

(56) References Cited

U.S. PATENT DOCUMENTS

4,442,436 A *	4/1984	Newcomb H01Q 5/321
	014000	343/722
4,764,773 A *	8/1988	Larsen H01Q 1/1285

(10) Patent No.: US 9,553,368 B1

(45) **Date of Patent: Jan. 24, 2017**

4,806,944	A *	2/1989	Jacomb-Hood	H01Q 3/26
				343/745
4,939,525	A *	7/1990	Brunner	
				343/708
6,429,821	B1 *	8/2002	Lewis, Jr	
				343/749
7,834,814	B2 *	11/2010	Xie	
				343/740

* cited by examiner

Primary Examiner — Tho G Phan (74) Attorney, Agent, or Firm — James M. Kasischke; Michael P. Stanley

(57) ABSTRACT

An antenna includes a first antenna section that can be joined to an antenna feed. The first section has conductive elements in series with reactive loads. The reactive loads are positioned with a regular spacing. The reactive loads and spacing are optimized for operation of the first section at the highest frequency. Additional antenna sections having successively lower frequencies are joined in series to the first antenna section. Each additional section has conductive elements joined in series with reactive loads at a particular spacing. The additional sections spacing and reactive loads are provided to work in conjunction with the higher frequency antenna sections to optimize the antenna for an additional frequency. A method for making such an antenna is further provided.

19 Claims, 3 Drawing Sheets

